

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:

VetOne Activated Charcoal Paste

AS SOLD BY VETONE

A Service of

COMPAS

MATERIAL SAFETY DATA SYSTEMS

www.compasmsds.com

PRODUCT NAME: ACTIVATED CHARCOAL PASTE

This Material Safety Data Sheet is being provided to your company, for the purpose of providing current health and safety information to your management and employees who work with this product. Please read the data provided and then provide it to those people at your company who have the responsibility to insure compliance with both FEDERAL and STATE Right to Know regulations, and to those employees that request information on this product.

Federal Regulations: Parts 29 and 42 Code of Federal Regulations.**State of Illinois:** Public Act 83-240**SECTION 1 - PRODUCT IDENTIFICATION**

Manufacturer: First Priority, Inc.
1585 Todd Farm Drive
Elgin, IL 60123-1146

Telephone Number: 800-650-4899
Emergency Number: Chemtrec
800-424-9300

Chemical Family: First Aid Gel

Formula: Mixture

Hazard Classification: Hazardous

HMIS Rating System: Health-1/Flammability-3/Reactivity-0

SECTION 2 - HAZARDOUS COMPONENTS

Ingredient	CAS#	PEL/TLV	Percent
Attapulgite	12174-11-7 1309-48-4 14808-60-7	NE	20.0% (w/w)
Charcoal Activated	7440-44-0	NE	10.0% (w/w)
Potassium Chloride	7447-40-7	NE	3.5% (w/w)
Polysorbate 80	9005-65-6	NE	13.0% (w/w)

The hazard communication standard requires that such mixtures be assumed to present the same health hazard as do components that constitute as least 1% of the mixture (0.1% for carcinogens) although OSHA has noted that the hazards of individual components may be altered by including them in a mixture. Some of the ingredients of this mixture are a trade secret. NE = not established.

SECTION 3 - PHYSICAL DATA

Boiling Point:	N/A	Specific Gravity:	N/A
Vapor Pressure:	N/A	Percent Volatile:	N/A
Vapor Density:	N/A	Evaporation Rate:	N/A
Solubility in Water:	Slightly soluble	Appearance & Odor:	Black colored paste

PRODUCT NAME: ACTIVATED CHARCOAL PASTE

SECTION 4 - FIRE & EXPLOSION DATA

Flash Point (Method): N/A
Estimated Flammable Limits in Air: NE
Extinguishing Media: Water, carbon dioxide or foam, Class A, BC or ABC fire extinguisher.
Special Fire Fighting Procedures: Must wear MSHA/NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.
Unusual Fire & Explosion Hazards: Avoid excessive heat.

SECTION 5 - HEALTH HAZARD DATA**Effects Of Overexposure**

Eyes: May cause irritation.
Skin: May cause irritation.
Inhalation: May cause irritation to respiratory tract.
Ingestion: No adverse effects expected, if ingested in small quantity.

Emergency First Aid Procedures:

Eye Contact: Flush eyes with large amounts of water for at least 15 minutes.
Skin Contact: Flush with large amounts of water.
Inhalation: Remove to fresh air. Get immediate medical attention.
Ingestion: If swallowed, immediately give 3-4 glasses of water. Get immediate medical attention.

SECTION 6 - REACTIVITY DATA

Stability: Stable
Conditions to avoid instability: None known.
Incompatibility: None known.
Hazardous Decomposition Byproducts: Will not occur.
Hazardous Polymerization: Will not occur.

SECTION 7 - SPILL OR LEAK PROCEDURES**Steps To Be Taken In Case Of Large Amount Of Material Is Released Or Spilled:**

Sweep or scoop up and place in chemical waste containers. Wash area with soap and water. In normal use this product is suitable for entry into an ordinary sanitary sewer system.

Waste Disposal Methods:

Dispose in accordance with all local, state and federal regulations. Contaminated absorbent may be deposited in a landfill in accordance with local, state and federal regulations.

